



Gloss Carbon/White/Red

S-WORKS EPIC CARBON 29

93414-0002	SM	Gloss Carbon/White/Red	
93414-0003	MD		
93414-0004	LG		
93414-0005	XL		
93414-0102	SM	Gloss Red/Silver/Black	
93414-0103	MD		
93414-0104	LG		
93414-0105	XL		

BIKE SPECS

	FACT 11m carbon front triangle, SWAT EMT tool cradle, 29" geometry, FACT IS construction, full FACT carbon rear triangle, tapered headtube, carbon PF30 BB, full internal shift/brake routing, 142mm dropouts, sealed cartridge bearing pivots, replaceable derailleur hanger, 100mm
	FOX/Specialized remote Mini-Brain w/ AUTOSAG, Kashima coating, inertia valve w/ Kevlar hose, Brain Fade adjust, 205x53mm, 100mm travel
	Custom RockShox SID World Cup 29 Brain, inertia valve damper, Solo Air spring, tapered carbon crown/steerer, top-mount Brain Fade and rebound adj., 15mm thru-axle, 100mm travel
	1-1/8 and 1-1/2" threadless, Campy style upper with 1-1/2" lower, cartridge bearings
	Syntax F109, 6-degree rise, 31.8mm clamp
	S-Works XC, flat bar, carbon, 700mm wide, 8-degree backsweep, 31.8mm
	Specialized Sip Grip, light lock-on, half-waffle aramid-infused, S/M: regular, Others: XL thickness
	Shimano XTR hydraulic disc, post mount, Ti/metal pad, Ice Tech, 160mm rotor
	Shimano XTR hydraulic disc, post mount, Ti/metal pad, Ice Tech, 160mm rotor
	Shimano XTR 985 hydraulic, w/I-Spec clamps
	Shimano XTR M986, direct mount, down-swing, dual-pull
	Shimano Shadow Plus XTR, 10-speed, GS mid cage
	Shimano XTR, 10-speed
	Shimano XTR M980, 10-speed, 11-36
	Shimano XTR 981
	S-Works OS carbon, integrated 1-piece spider, 10-speed XC double, SRAM rings, S: 170mm, Others: 175mm
	24/38 SRAM Rings
	PF30, OS press-in bearings, sealed cartridge
	Resin Test Ride Pedals with toe clips, CEN std.
	Roval Control SL 29, carbon disc, 22mm internal width, 24h/28h
	Roval Control SL 29, alloy hub body w/ Labyrinth seal design, 15mm thru-axle, 24h
	Roval Control SL 29 142+, DT Swiss Star Ratchet, 12mm thru-axle, 28h
	DT Swiss Revolution, 2.0/1.5/2.0mm stainless
	S-Works Fast Trak, 2Bliss Ready, 29x2.0", foldable aramid bead, 120 TPI
	S-Works Fast Trak, 2Bliss Ready, 29x2.0", foldable aramid bead, 120 TPI
	Ultralight presta valve
	Body Geometry Phenom Expert, hollow T1 rails, 143mm
	Specialized carbon, single bolt, 30.9mm, S: 350mm, Others: 400mm
	Specialized 7050 hard anodized alloy, single bolt, 31.8mm
	SWAT MTB XC Kit w/ bottle cages, EMT Tool, and Top Cap Chain Tool



Gloss Carbon/White/Red

S-WORKS EPIC CARBON 29 WORLD CUP

93414-0302	SM	Gloss Carbon/White/Red
93414-0303	MD	
93414-0304	LG	
93414-0305	XL	



BIKE SPECS

	FACT 11m carbon front triangle, SWAT EMT tool cradle, 29" World Cup geometry, FACT IS construction, full FACT carbon rear triangle, World Cup mega-chainslats, single ring only, tapered headtube, carbon PF30 BB, full internal shift/brake routing, 142mm dropouts, sealed cartridge bearing pivots, replaceable derailleur hanger, 95mm
	FOX/Specialized remote Mini-Brain w/ AUTOSAG, Kashima coating, inertia valve w/ Kevlar hose, Brain Fade adjust, 200x48mm, 95mm travel
	Custom RockShox SID World Cup 29 Brain, inertia valve damper, Solo Air spring, tapered carbon crown/steerer, top-mount Brain Fade and rebound adj., 15mm thru-axle, 95mm travel
	1-1/8 and 1-1/2" threadless, Campy style upper with 1-1/2" lower, cartridge bearings
	Syntace F109, 6-degree rise, 31.8mm clamp
	S-Works XC, flat bar, carbon, 700mm wide, 8-degree backsweep, 31.8mm
	Specialized Sip Grip, light lock-on, half-waffle aramid-infused, S/M: regular, Others: XL thickness
	Magura MT8, hydraulic disc, Hi Friction pad, alloy caliper, Storm SL rotor, S/M: 160mm, L/XL: 180mm rotor
	Magura MT8, hydraulic disc, Hi Friction pad, alloy caliper, Storm SL rotor, 160mm rotor
	Magura MT8, carbon master cylinder/lever blade, hollow lever pivot, reach adj.
	SRAM XX1 Type 2, 11-speed
	SRAM XX1, 11-speed, carbon/aluminum trigger, w/ MatchMaker clamp
	SRAM XX1, 11-speed, 10-42
	SRAM XX1, 11-speed, hollow plates/pins, PowerLink
	S-Works OS carbon, integrated 1-piece spider, custom SRAM XX1 chainring, S: 170mm, Others: 175mm
	34T, 32T ring included
	PF30, OS press-in bearings, sealed cartridge
	Resin Test Ride Pedals with toe clips, CEN std.
	Roval Control SL 29, carbon disc, 22mm internal width, 24h/28h
	Roval Control SL 29, alloy hub body w/ Labyrinth design, 15mm thru-axle, 24h
	Roval Control SL 29 142+, DT Swiss Star Ratchet, XX1 driver body, 12mm thru-axle, 28h
	DT Swiss Revolution, 2.0/1.5/2.0mm stainless
	S-Works Fast Trak, 2Bliss Ready, 29x2.0", foldable aramid bead, 120 TPI
	S-Works Renegade, 2Bliss Ready, 29x2.0", foldable aramid bead, 120 TPI
	Ultralight presta valve
	Body Geometry Phenom Expert, hollow Ti rails, 143mm
	Specialized carbon, single bolt, 30.9mm, S: 350mm, Others: 400mm
	Specialized 7050 hard anodized alloy, single bolt, 31.8mm
	SWAT Technology compatible (not included)



Gloss Candy Red/Gold

S-WORKS EPIC CARBON 29 FRAMESET

73414-0202	SM	Gloss Candy Red/Gold	
73414-0203	MD		
73414-0204	LG		
73414-0205	XL		
73414-0002	SM	Gloss Carbon/White/Red	
73414-0003	MD		
73414-0004	LG		
73414-0005	XL		
73414-0102	SM	Gloss Red/Silver/Black	
73414-0103	MD		
73414-0104	LG		
73414-0105	XL		
73414-0402	SM	Satin Carbon/Charcoal	
73414-0403	MD		
73414-0404	LG		
73414-0405	XL		

BIKE SPECS

	FACT 11m carbon front triangle, SWAT EMT tool cradle, 29" geometry, FACT IS construction, full FACT carbon rear triangle, tapered headtube, carbon PF30 BB, full internal shift/brake routing, 142mm dropouts, sealed cartridge bearing pivots, replaceable derailleur hanger, 100mm
	FOX/Specialized remote Mini-Brain w/ AUTOSAG, Kashima coating, inertia valve w/ Kevlar hose, Brain Fade adjust, 205x53mm, 100mm travel
	Custom RockShox SID World Cup 29 Brain, inertia valve damper, Solo Air spring, tapered carbon crown/steerer, top-mount Brain Fade and rebound adj., 15mm thru-axle, 100mm travel
	1-1/8 and 1-1/2" threadless, Campy style upper with 1-1/2" lower, cartridge bearings
	Specialized carbon, 2-bolt, 27.2mm, S: 350mm, Others: 400mm
	Specialized 7050 hard anodized alloy, single bolt, 31.8mm
	SWAT Technology compatible (not included)



Gloss Liquid Silver/Black

S-WORKS EPIC CARBON 29 WORLD CUP FRAMESET

73414-0602	SM	Gloss Liquid Silver/Black
73414-0603	MD	
73414-0604	LG	
73414-0605	XL	



BIKE SPECS

	FACT 11m carbon front triangle, SWAT EMT tool cradle, 29" World Cup geometry, FACT IS construction, full FACT carbon rear triangle, World Cup mega-chainstays, single ring only, tapered headtube, carbon PF30 BB, full internal shift/brake routing, 142mm dropouts, sealed cartridge bearing pivots, replaceable derailleur hanger, 95mm
	FOX/Specialized remote Mini-Brain w/ AUTOSAG, Kashima coating, inertia valve w/ Kevlar hose, Brain Fade adjust, 200x48mm, 95mm travel
	Custom RockShox SID World Cup 29 Brain, inertia valve damper, Solo Air spring, tapered carbon crown/steerer, top-mount Brain Fade and rebound adj., 15mm thru-axle, 95mm travel
	1-1/8 and 1-1/2" threadless, Campy style upper with 1-1/2" lower, cartridge bearings
	Specialized carbon, 2-bolt, 27.2mm, S: 350mm, Others: 400mm
	Specialized 7050 hard anodized alloy, single bolt, 31.8mm
	SWAT Technology compatible (not included)



Gloss Carbon/Red/White

S-WORKS CAMBER CARBON 29

94714-0002	SM	Gloss Carbon/Red/White
94714-0003	MD	
94714-0004	LG	
94714-0005	XL	



BIKE SPECS

	FACT 11m carbon front triangle, 29" geometry, FACT IS construction, full FACT rear triangle, tapered headtube, carbon PF30 BB, full internal shift/brake/post routing, 142mm dropouts, sealed cartridge bearing pivots, replaceable derailleur hanger, 110mm travel
	Custom FOX Float CTD Factory w/ AUTOSAG and Boost Valve, Kashima coating, Climb, Trail, Descend settings w/ Trail and reb adj., 197x48mm
	FOX Float Factory 29, Kashima coating, FIT damper, air spring, tapered alloy steerer, comp, lockout, and reb adj., 15mm thru-axle, 110mm travel
	1-1/8 and 1-1/2" threadless, Hella Flush style upper with 1-1/2" lower, cartridge bearings
	Syntace F109, 6-degree rise, 31.8mm clamp
	Specialized XC Mini-Riser, carbon, 720mm wide, 10mm rise, 10-backsweep, 6-upsweep, 31.8mm
	Specialized Sip Grip, light lock-on, half-waffle aramid-infused, S/M: regular, Others: XL thickness
	Custom Formula T1 Racing, metallic pad, S/M: 180mm, Others: 200mm rotor
	Custom Formula T1 Racing, metallic pad, S/M: 160mm, Others: 180mm rotor
	Custom Formula T1 Racing, hydraulic disc, carbon lever, tool-less pad contact (FCS) and reach adj., SRAM compatible MiXmaster shifter mounts
	SRAM XX1 Type 2, 11-speed, mid cage
	SRAM XX1, 11-speed, carbon trigger, w/ MatchMaker clamp
	SRAM XX1, 11-speed, 10-42
	SRAM XX1, 11-speed, hollow plates/pins, PowerLink
	S-Works OS carbon, integrated 1-piece spider, custom SRAM XX1 chainring, S: 170mm, Others: 175mm
	32T, 38T included
	PF30, OS press-in bearings, sealed cartridge
	Resin Test Ride Pedals with toe clips, CEN std.
	Royal Control Trail SL 29, carbon disc, 21mm internal width, 32h
	Royal Control Trail SL 29, 15mm thru-axle end caps, 32h
	Royal Control SL 29 142+, DT Star Ratchet, XX1 driver body, 12mm thru-axle, 32h
	DT Swiss Super Comp, 2.0/1.65/1.8 stainless
	Specialized Ground Control, 2Bliss Ready, 29x2.3", foldable aramid bead, 60TPI
	Specialized Ground Control, 2Bliss Ready, 29x2.1", foldable aramid bead, 60 TPI
	Ultralight presta valve
	Body Geometry Henge Expert, Ti rails, 143mm
	Specialized Command Post IR, 3-position, internally routed adjustable height w/ air spring, remote operated, single bolt head, 30.9mm, 100mm travel
	7050 hard anodized alloy collar, single bolt, 34.9mm
	Bottle cage, EMT Tool, and Top Cap Chain Tool w/ SWAT Technology



Gloss Carbon/White

S-WORKS CAMBER CARBON 29 FRAME

74714-0002	SM	Gloss Carbon/White
74714-0003	MD	
74714-0004	LG	
74714-0005	XL	



BIKE SPECS

	FACT 11m carbon front triangle, 29" geometry, FACT IS construction, full FACT rear triangle, tapered headtube, carbon PF30 BB, full internal shift/brake/post routing, 142mm dropouts, sealed cartridge bearing pivots, replaceable derailleur hanger, 110mm travel
	Custom FOX Float CTD Factory w/ AUTOSAG and Boost Valve, Kashima coating, Climb, Trail, Descend settings w/ Trail and reb adj., 197x48mm
	1-1/8 and 1-1/2" threadless, Hella Flush style upper with 1-1/2" lower, cartridge bearings
	Specialized Command Post IR, 3-position, internally routed adjustable height w/ air spring, remote operated, single bolt head, 30.9mm, 100mm travel
	7050 hard anodized alloy collar, single bolt, 34.9mm
	Bottle cage w/ SWAT Technology compatible (not included)



Gloss Liquid Silver/Black

S-WORKS STUMPJUMPER FSR CARBON EVO 29

97514-0202	SM	Gloss Liquid Silver/Black
97514-0203	MD	
97514-0204	LG	
97514-0205	XL	



BIKE SPECS

	FACT 9m carbon front triangle, 29" EVO geometry, FACT IS construction, M5 alloy rear triangle, tapered headtube, PF30 BB, ISCG '05, internal Command Post IR routing, 142mm dropouts, sealed cartridge bearing pivots, replaceable derailleur hanger, 135mm travel
	Custom FOX Float CTD Factory w/ AUTOSAG and Boost Valve, Kashima coating, Climb, Trail, Descend settings and reb adj., 195x46mm
	RockShox Pike RCT3 29, Solo Air spring, tapered alloy steerer, comp, lockout, reb, and threshold adj., 15mm thru-axle, 140mm travel
	1-1/8 and 1-1/2" threadless, Campy style upper with 1-1/2" lower, cartridge bearings
	Syntace F109, 6-degree rise, 31.8mm clamp
	Specialized XC mini-riser, alloy, 750mm wide, 10mm rise, 10-backsweep, 6-upsweep, 31.8mm
	Specialized Sip Grip, light lock-on, half-waffle aramid-infused, S/M: regular, Others: XL thickness
	Custom Avid XO Trail World Cup, 4-piston caliper, steel backed metallic pad, S/M: 180mm, Others: 200mm rotor
	Custom Avid XO Trail World Cup, 4-piston caliper, steel backed metallic pad, S/M: 160mm rotor, Others: 180mm rotor
	Custom Avid XO, hydraulic disc, carbon blade w/ bearing, tool-less reach adj. w/ MatchMaker clamp
	SRAM XX1 Type 2, 11-speed, mid cage
	SRAM XX1, 11-speed, carbon trigger, w/ MatchMaker clamp
	SRAM XX1, 11-speed, 10-42
	SRAM XX1, 11-speed, hollow plates/pins, PowerLink
	S-Works OS carbon, custom SRAM XX1 32T chainring, S: 170mm, Others: 175mm
	32T, 30T included
	PF30, OS press-in bearings, sealed cartridge
	Resin Test Ride Pedals with toe clips, CEN std.
	Roval Traverse SL 29, carbon disc, hookless bead, 22mm internal width, 32h
	Roval Traverse SL 29, 15mm thru-axle end caps, 32h
	Roval Traverse SL 29 142+, DT Swiss Star Ratchet, XX1 driver body, 12mm thru-axle, 32h
	DT Swiss Super Comp, 2.0/1.65/1.8 stainless
	Specialized Butcher Control, 2Bliss Ready, 29x2.3", foldable aramid bead, dual-compound, 60TPI
	Specialized Purgatory Control, 2Bliss Ready, 29x2.3", foldable aramid bead, dual-compound, 60 TPI
	Ultralight presta valve
	Body Geometry Henge Expert, Ti rails, 143mm
	Specialized Command Post IR, 3-position, internally routed adjustable height w/ air spring, remote operated, single bolt head, 30.9mm, S:100mm, Others: 125mm travel
	7050 hard anodized alloy, single bolt, 34.9mm
	Bottle cage, EMT Tool, and Top Cap Chain Tool w/ SWAT Technology



Satin/Gloss Carbon/Red/White

S-WORKS STUMPJUMPER FSR CARBON 29

97514-0002	SM	Satin/Gloss Carbon/Red/White
97514-0003	MD	
97514-0004	LG	
97514-0005	XL	



BIKE SPECS

	FACT 11m carbon front triangle, 29" geometry, FACT IS construction, full FACT rear triangle, tapered headtube, carbon PF30 BB, ISCG '05, Internal Command Post IR routing, 142mm dropouts, sealed cartridge bearing pivots, replaceable derailleur hanger, 130mm travel
	FOX/Specialized remote Brain w/ AUTOSAG, smaller Brain reservoir, Kashima coating, inertia valve w/ Trail Tune, BrainFade adjust, 195x48mm
	FOX 34 CTD Factory 29, Kashima coating, air spring, tapered alloy steerer, Climb, Trail, Descend settings w/ Trail and reb adj., 15mm thru-axle, 130mm travel
	1-1/8 and 1-1/2" threadless, Campy style upper with 1-1/2" lower, cartridge bearings
	Syntace F109, 6-degree rise, 31.8mm clamp
	Specialized XC Mini-Riser, carbon, 720mm wide, 10mm rise, 10-backsweep, 6-upsweep, 31.8mm
	Specialized Sip Grip, light lock-on, half-waffle aramid-infused, S/M: regular, Others: XL thickness
	Custom Formula T1 Racing, metallic pad, S/M: 180mm, Others: 200mm rotor
	Custom Formula T1 Racing, metallic pad, S/M: 160mm, Others: 180mm rotor
	Custom Formula T1 Racing, hydraulic disc, carbon lever, tool-less pad contact (FCS) and reach adj., SRAM compatible MiXmaster shifter mounts
	SRAM XX1 Type 2, 11-speed, mid cage
	SRAM XX1, 11-speed, carbon/aluminum trigger, w/ MatchMaker clamp
	SRAM XX1, 11-speed, 10-42
	SRAM XX1, 11-speed, hollow plates/pins, PowerLink
	S-Works OS carbon, custom SRAM XX1 32T chainring, S: 170mm, Others: 175mm 32T, 30T included
	PF30, OS press-in bearings, sealed cartridge
	Resin Test Ride Pedals with toe clips, CEN std.
	Roval Control Trail SL 29, carbon disc, 21mm internal width, 32h
	Roval Control Trail SL 29, 15mm thru-axle end caps, 32h
	Roval Control SL 29 142+, DT Star Ratchet, XX1 driver body, 12mm thru-axle, 32h
	DT Swiss Super Comp, 2.0/1.65/1.8 stainless
	Specialized Purgatory Control, 2Bliss Ready, 29x2.3", foldable aramid bead, dual-compound, 60TPI
	Specialized Ground Control, 2Bliss Ready, 29x2.3", foldable aramid bead, 60 TPI
	Ultralight presta valve
	Body Geometry Henge Expert, Ti rails, 143mm
	Specialized Command Post IR, 3-position, internally routed adjustable height w/ air spring, remote operated, single bolt head, 30.9mm, S:100mm, Others: 125mm travel
	7050 hard anodized alloy, single bolt, 34.9mm
	Bottle cage, EMT Tool, and Top Cap Chain Tool w/ SWAT Technology



Satin/Gloss Carbon/Red/White

S-WORKS STUMPJUMPER FSR CARBON 29 FRAME

77514-0002	SM	Satin/Gloss Carbon/Red/White
77514-0003	MD	
77514-0004	LG	
77514-0005	XL	



BIKE SPECS

	FACT 11m carbon front triangle, 29" geometry, FACT IS construction, full FACT rear triangle, tapered headtube, carbon PF30 BB, ISCG '05, Internal Command Post IR routing, 142mm dropouts, sealed cartridge bearing pivots, replaceable derailleur hanger, 130mm travel
	FOX/Specialized remote Brain w/ AUTOSAG, smaller Brain reservoir, Kashima coating, inertia valve w/ Trail Tune, BrainFade adjust, 195x48mm
	1-1/8 and 1-1/2" threadless, Campy style upper with 1-1/2" lower, cartridge bearings
	Specialized Command Post IR, 3-position, internally routed adjustable height w/ air spring, remote operated, single bolt head, 30.9mm, S:100mm, Others: 125mm travel
	7050 hard anodized alloy, single bolt, 34.9mm
	Bottle cage w/ SWAT Technology compatible (not included)



Gloss/Satin Carbon/White

S-WORKS ENDURO CARBON 29

97714-0203	MD	Gloss/Satin Carbon/White
97714-0204	LG	
97714-0205	XL	



S-WORKS ENDURO CARBON 26

97714-0002	SM	Gloss/Satin Carbon/White
97714-0003	MD	
97714-0004	LG	



Gloss/Satin Carbon/White

BIKE SPECS

	FACT IS-X 11m carbon front triangle, 29"/26" geometry, FACT IS construction, M5 rear triangle, tapered headtube, PF30 BB, ISCG .05 mounts, internal Command Post IR routing, 142+ dropouts, full cartridge bearing pivots, replaceable derailleur hanger, 29" : 155mm travel; 26" : 165mm travel
	Custom Cane Creek Double Barrel Air, high/low speed comp and reb adj., climb switch, 216x64mm
	RockShox Pike RCT3 29 / 26 . Solo Air spring, tapered alloy steerer, comp, lockout, reb, and threshold adj., 15mm thru-axle, 160mm travel
	1-1/8 and 1-1/2" threadless, Campy style upper with 1-1/2" lower, cartridge bearings
	Syntace F109, 6-degree rise, 31.8mm clamp
	29" : Specialized XC Mini-Riser, carbon, 750mm wide, 10mm rise, 10-backsweep, 6-upsweep, 31.8mm / 26" : S-Works All-Mountain, low-rise, carbon, 750mm wide, 8-degree backsweep, 6-degree upsweep, 31.8mm
	Specialized Sip Grip, light lock-on, half-waffle aramid-infused, 29" : M: regular, Others: XL / 26" : S/M: regular, Others: XL thickness
	Custom Avid XO Trail, 4-piston caliper, steel backed metallic pad, 200mm rotor
	Custom Avid XO Trail, 4-piston caliper, steel backed metallic pad, 180mm rotor
	Custom Avid XO, hydraulic disc, carbon blade w/ bearing, tool-less reach adj. w/ MatchMaker clamp
	SRAM XX1 Type 2, 11-speed, mid cage
	SRAM XX1, 11-speed, carbon/aluminum trigger, w/ MatchMaker clamp
	SRAM XX1, 11-speed, 10-42
	SRAM XX1, 11-speed, hollow plates/pins, PowerLink
	SRAM XX1, carbon arms, PF30 spindle, 29" : single 30T ring, 175mm / 26" : single 32T ring, S: 170mm, Others: 175mm
	29" : 32T, 30T included; 26" : 34T, 32T ring included
	SRAM PF30, OS press-in bearings, sealed cartridge
	Resin Test Ride Pedals with toe clips, CEN std.
	Royal Traverse SL 29 / 26 , carbon disc, hookless bead, 23mm internal width, 29" : 32h; 26" : 27h/32h
	Royal Traverse SL 29 / 26 , 15mm thru-axle end caps, 29" : 32h / 26" : 27h
	Royal Traverse SL 29 / 26 142+, DT Swiss Star Ratchet, XX1 driver body, 12mm thru-axle, 32h
	DT Swiss Super Comp, 2.0/1.65/1.8 stainless
	Specialized Butcher Control, 2Bliss Ready, 29" x2.3" / 26" x2.3", foldable aramid bead, dual-compound, 60TPI
	Specialized Purgatory Control, 2Bliss Ready, 29" x2.3" / 26" x2.3", foldable aramid bead, dual-compound, 60 TPI
	Ultralight presta valve
	Body Geometry Henge Expert, Ti rails, 143mm
	Specialized Command Post IR, 3-position, internally routed adjustable height w/ air spring, remote operated, single bolt head, 30.9mm, S:100mm, Others: 125mm travel
	7050 hard anodized alloy collar, single bolt, 34.9mm
	Bottle cage w/ SWAT Technology compatible (not included)



Gloss Carbon/Hyper/White

S-WORKS ENDURO FSR CARBON 29 FRAME

77714-0703	MD	Gloss Carbon/Hyper/White
77714-0704	LG	
77714-0705	XL	



BIKE SPECS

	FACT IS-X 11m carbon front triangle, 29" geometry, FACT IS construction, M5 rear triangle, tapered headtube, PF30 BB, ISCG .05 mounts, internal Command Post IR routing, 142+ dropouts, full cartridge bearing pivots, replaceable derailleur hanger, 155mm travel
	Custom Cane Creek Double Barrel Air, high/low speed comp and reb adj., climb switch, 216x64mm
	1-1/8 and 1-1/2" threadless, Campy style upper with 1-1/2" lower, cartridge bearings
	SRAM, 10-speed, mid direct mount for Taco Blade, bottom pull (in parts box)
	Specialized Command Post IR, 3-position, internally routed adjustable height w/ air spring, remote operated, single bolt head, 30.9mm, 125mm travel
	7050 hard anodized alloy collar, single bolt, 34.9mm
	Bottle cage w/ SWAT Technology compatible (not included)



Gloss/Satin Carbon/Red/White

S-WORKS DEMO 8 CARBON

99914-0002	SM	Gloss/Satin Carbon/Red/White
99914-0003	MD	
99914-0004	LG	



BIKE SPECS

	FACT 11m front triangle, bonded alloy-insert BB and headtube, 135mm spacing M5 rear triangle, magnesium link, compact race design, ISCG .05 mount, cartridge bearing rear shock mount, rear derailleur protector, 200mm travel
	Custom 0hins TTX22M, coil over w/ piggy back, spherical bearing mount, high/low speed comp, reb adj., 9.5x3.0", S: 76x434lb, M: 84x479lb, L: 92x525lb
	RockShox Boxxer World Cup, Mission Control damper, Solo Air spring, alloy steerer, comp and reb adj. w/ bottom out control, 20mm Maxle DH thru-axle, 200mm travel
	1-1/2" integrated for 1-1/8" steerer, cartridge bearings
	Specialized Direct Mount, 6061 alloy, 4-bolt, 31.8mm clamp
	Renthal DH, low-rise, carbon, 780mm wide, 8-degree backsweep, 6-degree upsweep, 31.8mm
	Specialized Sip Grip, light lock-on, half-waffle aramid-infused, S/M: regular, L: XL thickness
	Custom Avid Code X0 World Cup, hydraulic disc, Code caliper, organic pad, stainless hardware, 200mm rotor
	Custom Avid Code X0 World Cup, hydraulic disc, Code caliper, organic pad, stainless hardware, 180mm rotor
	Custom Avid Code X0 World Cup, hydraulic disc, X0 lever, tool-less reach
	SRAM XO, 9-speed, short cage
	SRAM XO, 9-speed, carbon/aluminum trigger, w/ MatchMaker clamp
	Shimano HG-70 Capreo, 7-speed, Micro 9-20
	KMC X9 SL, nickel plate, reusable Missing Link
	SRAM XO DH, carbon arms, PF30 spindle, 165mm, E.13 SRS chainguide
	micro-single 32T ring
	SRAM PF30 DH, 83mm shell
	Specialized Bennies, 6061 alloy body, sealed cartridge, 4.5mm removable pins
	Royal DH 26, alloy disc, 30mm wide w/eyelets, 32h
	Specialized Hi Lo disc, sealed cartridge bearings, 20mm thru-axle, 32h
	Custom DT Swiss, Capreo compatible, Star Ratchet, 135mm, 32h
	DT Competition Stainless, 3X front/rear 2.0
	Specialized Butcher DH, 26x2.5", wire bead, soft dual compound, 60 TPI
	Specialized Butcher DH, 26x2.5", wire bead, soft dual compound, 60 TPI
	Standard presta valve
	Body Geometry Phenom Comp, hollow Cr-Mo rails, 143mm
	Thomson alloy straight w/ 12-degree clamp, 367mm
	Specialized 7050 hard anodized alloy, single bolt, 36.9mm



Gloss/Satin Liquid Silver/Carbon

S-WORKS DEMO 8 CARBON FRAME

79914-0302	SM	Gloss/Satin Liquid Silver/Carbon	
79914-0303	MD		
79914-0304	LG		
79914-0002	SM	Gloss/Satin Carbon/Red/White	
79914-0003	MD		
79914-0004	LG		

BIKE SPECS

	FACT 11m front triangle, bonded alloy-insert BB and headtube, 150mm spacing M5 rear triangle, magnesium link, compact race design, ISCG .05 mount, cartridge bearing rear shock mount, rear derailleur protector, 200mm travel
	Custom Ohlins TTX22M, coil over w/ piggy back, spherical bearing mount, high/low speed comp. reb adj., 9.5x3.0", S: 76x434lb, M: 84x479lb, L: 92x525lb
	1-1/2" integrated for 1-1/8" steerer, cartridge bearings
	SRAM PF30 to BSA 83mm adapter
	Thomson alloy straight w/ 12-degree clamp, 367mm
	Specialized 7050 hard anodized alloy, single bolt, 36.9mm

S-WORKS DEMO FSR CARBON FRAME TLD EDITON

73E7-0302	SM	TLD Edition	
73E7-0303	MD		
73E7-0304	LG		

BIKE SPECS

	FACT 11m front triangle, bonded alloy-insert BB and HT, 150mm spacing M5 rear triangle, magnesium link, compact race design, ISCG .05 mount, cartridge bearing rear shock mount, rear derailleur protector, 200mm travel
	Cane Creek Double Barrel, coil over w/piggy back, high/low speed compression and high/low speed rebound adj., 9.5x3", S:350, M:400, L:450
	1-1/2" integrated for 1-1/8" steerer, cartridge bearings
	SRAM PF30 to BSA 83mm adapter
	Thomson alloy straight w/ 12-degree clamp, 367mm
	Specialized 7050 hard anodized alloy, 36.9mm, single bolt



TLD Edition



Gloss Red/Silver/Black

S-WORKS STUMPJUMPER HT CARBON 29

97114-0115	15.5"	Gloss Red/Silver/Black	
97114-0117	17.5"		
97114-0119	19"		
97114-0121	21"		
97114-0015	15.5"	Gloss Carbon/White/Red	
97114-0017	17.5"		
97114-0019	19"		
97114-0021	21"		

BIKE SPECS

	FACT 11m carbon, 29" geometry, FACT IS construction, tapered headtube, carbon PF30 BB, full internal shift/brake routing, 142+ dropouts, PM 160 rear brake, replaceable alloy rear derailleur hanger
	Custom RockShox SID World Cup 29 Brain, inertia valve damper, Solo Air spring, tapered carbon crown/steerer, top-mount Brain Fade and rebound adj., 15mm thru-axle, S: 80mm, Others: 90mm travel
	1-1/8 and 1-1/2" threadless, Campy style upper with 1-1/2" lower, cartridge bearings
	Syntace F109, 6-degree rise, 31.8mm clamp
	S-Works XC, flat bar, carbon, 700mm wide, 8-degree backsweep, 31.8mm
	Specialized Sip Grip, light lock-on, half-waffle aramid-infused, S/M: regular, Others: XL thickness
	Shimano XTR hydraulic disc, post mount, Ti/metal pad, Ice Tech, 160mm rotor
	Shimano XTR hydraulic disc, post mount, Ti/metal pad, Ice Tech, 160mm rotor
	Shimano XTR 985 hydraulic, w/I-Spec clamps
	Shimano XTR M986, down-swing, 34.9mm clamp, dual-pull
	Shimano Shadow Plus XTR, 10-speed, GS mid cage
	Shimano XTR, 10-speed
	Shimano XTR M980, 10-speed, 11-36
	Shimano XTR 981
	S-Works OS carbon, integrated 1-piece spider, 10-speed XC double, SRAM rings, S: 170mm, Others: 175mm
	38/24
	PF30, OS press-in bearings, sealed cartridge
	Resin Test Ride Pedals with toe clips, CEN std.
	Roval Control SL 29, carbon disc, 22mm internal width, 24h/28h
	Roval Control SL 29, alloy hub body w/ Labyrinth seal design, 15mm thru-axle, 24h
	Roval Control SL 29 142+, DT Swiss Star Ratchet, 12mm thru-axle, 28h
	DT Swiss Revolution, 2.0/1.5/2.0mm stainless
	S-Works Fast Trak, 2Bliss Ready, 29x2.0", foldable aramid bead, 120 TPI
	S-Works Fast Trak, 2Bliss Ready, 29x2.0", foldable aramid bead, 120 TPI
	Ultralight presta valve
	Body Geometry Phenom Expert, hollow TI rails, 143mm
	Specialized carbon, 2-bolt, 27.2mm, S: 350mm, Others: 400mm
	Specialized 7050 hard anodized alloy, single bolt, 31.8mm
	Bottle cage, EMT Tool, and Top Cap Chain Tool w/ SWAT Technology



Gloss Carbon/White/Red

S-WORKS STUMPJUMPER HT CARBON 29 WORLD CUP

97114-0315	15.5"	Gloss Carbon/White/Red
97114-0317	17.5"	
97114-0319	19"	
97114-0321	21"	



BIKE SPECS

	FACT 11m carbon, 29" geometry, FACT IS construction, tapered headtube, carbon PF30 BB, full internal shift/brake routing, 142+ dropouts, PM 160 rear brake, replaceable alloy rear derailleur hanger
	Custom RockShox SID World Cup 29 Brain, inertia valve damper, Solo Air spring, tapered carbon crown/steerer, top-mount Brain Fade and rebound adj., 15mm thru-axle, S: 80mm, Others: 90mm travel
	1-1/8 and 1-1/2" threadless, Campy style upper with 1-1/2" lower, cartridge bearings
	Syntace F109, 6-degree rise, 31.8mm clamp
	S-Works XC, flat bar, carbon, 700mm wide, 8-degree backsweep, 31.8mm
	Specialized Sip Grip, light lock-on, half-waffle aramid-infused, S/M: regular, L/XL: XL thickness
	Magura MT8, hydraulic disc, Hi Friction pad, alloy caliper, Storm SL rotor, S/M: 160mm, L/XL: 180mm rotor
	Magura MT8, hydraulic disc, Hi Friction pad, alloy caliper, Storm SL rotor, 160mm rotor
	Magura MT8, carbon master cylinder/lever blade, hollow lever pivot, reach adj.
	SRAM XX1 Type 2, 11-speed
	SRAM XX1, 11-speed, carbon/aluminum trigger, w/ MiXmaster clamp
	SRAM XX1, 11-speed, 10-42
	SRAM XX1, 11-speed, hollow plates/pins, PowerLink
	S-Works OS carbon, integrated 1-piece spider, custom SRAM XX1 chainring, S: 170mm, Others: 175mm
	34T installed, 32T in parts box
	PF30, OS press-in bearings, sealed cartridge
	Resin Test Ride Pedals with toe clips, CEN std.
	Roval Control SL 29, carbon disc, 22mm internal width, 24h/28h
	Roval Control SL 29, alloy hub body w/ Labyrinth seal design, 15mm thru-axle, 24h
	Roval Control SL 29 142+, DT Swiss Star Ratchet, XX1 driver body, 12mm thru-axle, 28h
	DT Swiss Revolution, 2.0/1.5/2.0mm stainless
	S-Works Fast Trak, 2Bliss Ready, 29x2.0", foldable aramid bead, 120 TPI
	S-Works Renegade, 2Bliss Ready, 29x2.0", foldable aramid bead, 120 TPI
	Ultralight presta valve
	Body Geometry Phenom Expert, hollow T1 rails, 143mm
	Specialized carbon, single bolt, 27.2mm, S: 350mm, Others: 400mm
	Specialized 7050 hard anodized alloy, 2-bolt, 31.8mm
	Bottle cage w/ SWAT Technology compatible (not included)



Gloss Red/Silver/Black

S-WORKS STUMPJUMPER HT CARBON 29 FRAMESET

77114-0215	15.5"	Gloss Red/Silver/Black	
77114-0217	17.5"		
77114-0219	19"		
77114-0221	21"		
77114-0415	15.5"	Satin Carbon/Charcoal	
77114-0417	17.5"		
77114-0419	19"		
77114-0421	21"		
77114-0515	15.5"	Gloss Candy Red/Gold	
77114-0517	17.5"		
77114-0519	19"		
77114-0521	21"		

BIKE SPECS



FACT 11m carbon, 29" geometry, FACT IS construction, tapered headtube, carbon PF30 BB, full internal shift/brake routing, 142+ dropouts, PM 160 rear brake, replaceable alloy rear derailleur hanger



Custom RockShox SID World Cup 29 Brain, inertia valve damper, Solo Air spring, tapered carbon crown/steerer, top-mount Brain Fade and rebound adj., 15mm thru-axle, S: 80mm, Others: 90mm travel



1-1/8 and 1-1/2" threadless, Campy style upper with 1-1/2" lower, cartridge bearings



Specialized carbon, single bolt, 27.2mm, S: 350mm, Others: 400mm



Specialized 7050 hard anodized alloy, single bolt, 31.8mm

Bottle cage w/ SWAT Technology compatible (not included)



S-WORKS ROAD





Satin/Gloss Carbon/Red

S-WORKS VENGE DI2 X2

99014-0249	49	Satin/Gloss Carbon/Red
99014-0252	52	
99014-0254	54	
99014-0256	56	
99014-0258	58	
99014-0261	61	



S-WORKS VENGE DA X2

99014-0049	49	Satin/Gloss Carbon/Red
99014-0052	52	
99014-0054	54	
99014-0056	56	
99014-0058	58	
99014-0061	61	



BIKE SPECS

	Specialized FACT 11r carbon, FACT construction, aero-shaped tubing, compact race design, tapered 1-1/8" to 1-3/8" headtube, internal cable routing, carbon OSBB
	S-Works FACT carbon full mono-coque, OS race for 1-3/8" bearing
	1-1/8" upper and 1-3/8" lower, hybrid cartridge lightweight bearings, w/ custom Venge top cap
	S-Works SL, 3D forged 7050 aluminum, 4-bolt, 31.8mm
	S-Works Tarmac Bend, FACT carbon, 140mm drop, 85mm reach
	Specialized SL
	Shimano Dura-Ace
	Shimano Dura-Ace
	DI2: Shimano Dura-Ace Di2 / DA: Shimano Dura-Ace
	DI2: Shimano Dura-Ace Di2, braze-on, 11-speed / DA: Shimano Dura-Ace, braze-on, 11-speed
	DI2: Shimano Dura-Ace Di2, 11-speed / DA: Shimano Dura-Ace, 11-speed
	DI2: Shimano Dura-Ace Di2 STI, 11-speed / DA: Shimano Dura-Ace STI, 11-speed
	Shimano Dura-Ace, 11-speed, 11-28
	Shimano Dura-Ace, 11-speed
	S-Works FACT carbon, OSBB
	53/39
	OS integrated, CeramicSpeed, sealed ceramic bearings
	Nylon flat test ride, loose ball, w/ reflectors
	Roval Rapide CLX 60, w/ CeramicSpeed bearings
	Roval Rapide CLX 60, w/ CeramicSpeed bearings
	S-Works Turbo, 220TPI, foldable aramid bead, BlackBelt protection, 700x24c
	S-Works Turbo, 220TPI, foldable aramid bead, BlackBelt protection, 700x24c
	Lightweight, 80mm presta valve
	Body Geometry Romin Evo Pro, carbon rails, 143mm
	S-Works Venge, FACT carbon, flippable 20/0mm offset
	Venge integrated seat clamp assembly



Satin/Gloss Carbon/Red



Gloss Blue/Hyper/Black

S-WORKS VENGE FRAMESET

79014-0249	49	Gloss Blue/Hyper/Black
79014-0252	52	
79014-0254	54	
79014-0256	56	
79014-0258	58	
79014-0261	61	



7728-1049	49	Quickstep
7728-1052	52	
7728-1054	54	
7728-1056	56	
7728-1058	58	
7728-1061	61	



79014-0049	49	Satin/Gloss Carbon/Red
79014-0052	52	
79014-0054	54	
79014-0056	56	
79014-0058	58	
79014-0061	61	



79014-0349	49	Gloss Metallic Silver/Black/Red
79014-0352	52	
79014-0354	54	
79014-0356	56	
79014-0358	58	
79014-0361	61	



BIKE SPECS



Specialized FACT 11r carbon, FACT construction, aero-shaped tubing, compact race design, tapered 1-1/8" to 1-3/8" headtube, internal cable routing, carbon OSBB



S-Works FACT carbon full monocoque, OS race for 1-3/8" bearing



1-1/8" upper and 1-3/8" lower, hybrid cartridge lightweight bearings, w/ custom Venge top cap



OS integrated, CeramicSpeed, sealed ceramic bearings



S-Works Venge, FACT carbon, flippable 20/0mm offset



Venge integrated seat clamp assembly



Satin/Gloss Carbon/Red

S-WORKS TARMAC SL4 DI2 X2

97014-0249	49	Satin/Gloss Carbon/Red
97014-0252	52	
97014-0254	54	
97014-0256	56	
97014-0258	58	
97014-0261	61	



S-WORKS TARMAC SL4 DA X2

97014-0049	49	Satin/Gloss Carbon/Red
97014-0052	52	
97014-0054	54	
97014-0056	56	
97014-0058	58	
97014-0061	61	



BIKE SPECS

	S-Works SL4 FACT 11r carbon, FACT construction, tapered/shaped headtube, compact race design, 1-3/8" lower headset bearing, carbon OSBB
	S-Works Tarmac FACT carbon full monocoque, OS race for 1-3/8" bearing, hollow carbon dropouts
	1-1/8" upper and 1-3/8" lower, hybrid cartridge lightweight bearings, 8mm carbon cone spacer, w/ 20mm of carbon spacers
	S-Works SL, 3D forged 7050 aluminum, 4-bolt, 31.8mm
	S-Works Tarmac Bend, FACT carbon, 140mm drop, 85mm reach
	Specialized SL
	Shimano Dura-Ace
	Shimano Dura-Ace
	DI2: Shimano Dura-Ace Di2 / DA: Shimano Dura-Ace
	DI2: Shimano Dura-Ace Di2, braze-on, 11-speed / DA: Shimano Dura-Ace, braze-on, 11-speed
	DI2: Shimano Dura-Ace Di2, 11-speed / DA: Shimano Dura-Ace, 11-speed
	DI2: Shimano Dura-Ace Di2 STI, 11-speed / DA: Shimano Dura-Ace STI, 11-speed
	Shimano Dura-Ace, 11-speed, 11-28
	Shimano Dura-Ace, 11-speed
	S-Works FACT carbon, OSBB
	53/39
	OS integrated, CeramicSpeed, sealed ceramic bearings
	Nylon flat test ride, loose ball, w/ reflectors
	Roval Rapide CLX 40, w/ CeramicSpeed bearings
	Roval Rapide CLX 40, w/ CeramicSpeed bearings
	S-Works Turbo, 220TPI, foldable aramid bead, BlackBelt protection, 700x24c
	S-Works Turbo, 220TPI, foldable aramid bead, BlackBelt protection, 700x24c
	Turbo Ultralight, 60mm presta valve
	Body Geometry Toupé Pro, carbon rails, 143mm
	S-Works SL, FACT carbon, 2-bolt, 27.2mm
	Forged alloy, Ti bolt, 32.6mm



Satin/Gloss Carbon/Red



Gloss/Satin/Orange/Carbon/White

S-WORKS TARMAC SL4 FRAMESET

77E0-0349	49	Team Saxo/Tinkoff	
77E0-0352	52		
77E0-0354	54		
77E0-0356	56		
77E0-0358	58		
77E0-0361	61		
77014-0149	49	Satin/Gloss/Carbon/Red	
77014-0152	52		
77014-0154	54		
77014-0156	56		
77014-0158	58		
77014-0161	61		
77014-0249	49	Gloss/Satin/Orange/Carbon/White	
77014-0252	52		
77014-0254	54		
77014-0256	56		
77014-0258	58		
77014-0261	61		
77014-0349	49	Race Black	
77014-0352	52		
77014-0354	54		
77014-0356	56		
77014-0358	58		
77014-0361	61		
77014-0849	49	Satin/Gloss/White/Carbon/Red	
77014-0852	52		
77014-0854	54		
77014-0856	56		
77014-0858	58		
77014-0861	61		

BIKE SPECS

	S-Works SL4 FACT 11r carbon, FACT construction, tapered/shaped headtube, compact race design, 1-3/8" lower headset bearing, carbon OSBB
	S-Works Tarmac FACT carbon full mono-coque, OS race for 1-3/8" bearing, hollow carbon dropouts
	1-1/8" upper and 1-3/8" lower, hybrid cartridge lightweight bearings, 8mm carbon cone spacer, w/ 20mm of carbon spacers
	OS integrated, CeramicSpeed, sealed ceramic bearings
	S-Works SL, FACT carbon, 2-bolt, 27.2mm
	Forged alloy, 32.6mm, Ti bolt



Dual Ano Black/Silver/Red
(Drawing similar to real bike)

S-WORKS ALLEZ C2

94614-0049	49	Dual Ano Black/Silver/Red
94614-0052	52	
94614-0054	54	
94614-0056	56	
94614-0058	58	
94614-0061	61	



BIKE SPECS

	Specialized S-Works Smartweld E5 alloy, hydroformed aluminum tubing, 1-3/8" lower bearing, OSBB
	Specialized S-Works Tarmac, FACT carbon full monocoque, carbon steerer/crown for 1-3/8" lower bearing
	1-1/8" upper and 1-3/8" lower Cr-Mo cartridge bearings integrated w/ headset, 8mm cone spacer, w/ 20mm of carbon spacers
	Specialized S-Works SL, 4-bolt, 31.8mm clamp
	Specialized S-Works Tarmac, FACT carbon, short drop
	Specialized S-Wrap microfiber, shockproof
	Shimano Dura-Ace 9000
	Shimano Dura-Ace 9000
	Shimano Dura-Ace 9000
	Shimano Dura-Ace 9000
	Shimano Dura-Ace 9000
	Shimano Dura-Ace 9000 STI
	Shimano Dura-Ace 9000, 11-speed
	KMC X11 SL
	Specialized FACT carbon, SRAM RED rings
	52/36
	BB30, ceramic bearings
	Nylon flat test ride, loose ball, w/ reflectors
	Roval Rapide CLX 40
	Roval Rapide CLX 40
	Specialized S-Works Turbo, 127TPI, aramid bead, BlackBelt protection, 700x24c
	Specialized S-Works Turbo, 127TPI, aramid bead, BlackBelt protection, 700x24c
	Standard presta valve, long stem
	Body Geometry Toupe Pro, FACT carbon rails, 143mm
	Specialized S-Works, FACT carbon, 27.2mm
	Alloy, 31.8mm



Dual Ano Black/Silver/Red
(Drawing similar to real bike)

S-WORKS ALLEZ FRAMESET

74614-0049	49	Dual Ano Black/Silver/Red
74614-0052	52	
74614-0054	54	
74614-0056	56	
74614-0058	58	
74614-0061	61	



BIKE SPECS

	Specialized S-Works Smartweld E5 alloy, hydroformed aluminum tubing, 1-3/8" lower bearing, OSBB
	Specialized S-Works Tarmac, FACT carbon full monocoque, carbon steerer/crown for 1-3/8" lower bearing
	1-1/8" Steel Upper/1-3/8" Steel Lower, Aluminum, 9Pc, 28.6/37.1/29.98, w/ Cartridge Cr-Mo Bearing
	BB30 Adapter-Mach-Turn-Xa
	OSBB, 2Pcs 6806LJb/C3 In Parts Box
	S-Works Carbon Fiber 27.2mm, 49/52=300mm, 54/56/58/60/64=350mm
	31.8mm Alloy, w/ Allen Bolt, w/ O Logo



Satin/Gloss Carbon/Red

S-WORKS ROUBAIX SL4 RED DISC C2

97314-0349	49	Satin/Gloss Carbon/Red
97314-0352	52	
97314-0354	54	
97314-0356	56	
97314-0358	58	
97314-0361	61	



BIKE SPECS

	S-Works SL4 FACT 11r carbon, FACT construction, tapered/shaped 1-1/8" to size-specific lower headtube, compact race design, Zertz, internal cable routing, carbon OSBB
	S-Works Roubaix FACT carbon full monocoque, disc-specific, Zertz, size-specific
	1-1/8" upper and size-specific lower, hybrid cartridge lightweight bearings, 8mm carbon cone spacer, w/ 20mm of carbon spacers
	S-Works Pro-Set, 3D forged 7050 aluminum, carbon-clip front, 4-degree shim, CNC head bolts, 31.8mm
	S-Works Shallow Drop, FACT carbon, 125mm drop, 75mm reach
	Specialized Roubaix, w/ S gel
	SRAM RED, hydraulic disc, 160mm rotor
	SRAM RED, hydraulic disc, 140mm rotor
	SRAM RED, hydraulic
	SRAM RED 22, braze-on, 11-speed, YAW, w/ chain spotter
	SRAM RED 22, 11-speed
	SRAM RED 22, DoubleTap, 11-speed
	SRAM RED 22, 11-speed, 11-28
	SRAM RED 22, w/ PowerLink
	S-Works FACT carbon, OSBB
	50/34
	OS integrated, CeramicSpeed, sealed ceramic bearings
	Nylon flat test ride, loose ball, w/ reflectors
	Roval Rapide CLX 40 Disc, w/ CeramicSpeed bearings
	Roval Rapide CLX 40 Disc, w/ CeramicSpeed bearings
	S-Works Turbo, 220TPI, foldable aramid bead, BlackBelt protection, 700x26c
	S-Works Turbo, 220TPI, foldable aramid bead, BlackBelt protection, 700x26c
	Turbo Ultralight, 60mm presta valve
	Body Geometry Romin Pro, carbon rails, 143mm
	S-Works CG-R, FACT carbon w/ Zertz, 27.2mm
	Forged alloy, Ti bolt, 32.6mm



Satin/Gloss Carbon/Red

S-WORKS ROUBAIX SL4 DA C2

97314-0049	49	Satin/Gloss Carbon/Red
97314-0052	52	
97314-0054	54	
97314-0056	56	
97314-0058	58	
97314-0061	61	



BIKE SPECS

	S-Works SL4 FACT 11r carbon, FACT construction, tapered/shaped 1-1/8" to size-specific lower headtube, compact race design, Zertz, internal cable routing, carbon OSBB
	S-Works Roubaix FACT carbon full monocoque, Zertz, size-specific, hollow carbon dropouts
	1-1/8" upper and size-specific lower, hybrid cartridge lightweight bearings, 8mm carbon cone spacer, w/ 20mm of carbon spacers
	S-Works Pro-Set, 3D forged 7050 aluminum, carbon-clip front, 4-degree shim, CNC head bolts, 31.8mm
	S-Works Shallow Drop, FACT carbon, 125mm drop, 75mm reach
	Specialized Roubaix, w/ S gel
	Shimano Dura-Ace
	Shimano Dura-Ace
	Shimano Dura-Ace, braze-on, 11-speed
	Shimano Dura-Ace, 11-speed
	Shimano Dura-Ace, 11-speed
	Shimano Dura Ace, 11-speed, 11-28
	Shimano Dura-Ace, 11-speed
	S-Works FACT carbon, OSBB
	50/34
	OS integrated, CeramicSpeed, sealed ceramic bearings
	Nylon flat test ride, loose ball, w/ reflectors
	Roval Rapide CLX 40, w/ CeramicSpeed bearings
	Roval Rapide CLX 40, w/ CeramicSpeed bearings
	S-Works Turbo, 220TPI, foldable aramid bead, BlackBelt protection, 700x26c
	S-Works Turbo, 220TPI, foldable aramid bead, BlackBelt protection, 700x26c
	Turbo Ultralight, 60mm presta valve
	Body Geometry Romin Pro, carbon rails, 143mm
	S-Works CG-R, FACT carbon w/ Zertz, 27.2mm
	Forged alloy, Ti bolt, 32.6mm



Satin/Gloss Carbon/Red

S-WORKS ROUBAIX SL4 FRAMESET

70E3-0349	49	Team Omega Pharma/Quick Step	
70E3-0352	52		
70E3-0354	54		
70E3-0356	56		
70E3-0358	58		
70E3-0361	61		
77314-0249	49	Satin/Gloss Carbon/Red	
77314-0252	52		
77314-0254	54		
77314-0256	56		
77314-0258	58		
77314-0261	61		
77314-0349	49	Gloss Silver/Black/Red	
77314-0352	52		
77314-0354	54		
77314-0356	56		
77314-0358	58		
77314-0361	61		
77314-0549	49	Gloss Candy Red/Tint Red/Black	
77314-0552	52		
77314-0554	54		
77314-0556	56		
77314-0558	58		
77314-0561	61		

S-WORKS ROUBAIX SL4 DISC FRAMESET

77314-0149	49	Gloss Silver/Black/Red	
77314-0152	52		
77314-0154	54		
77314-0156	56		
77314-0158	58		
77314-0161	61		

BIKE SPECS

	S-Works SL4 FACT 11r carbon, FACT construction, tapered/shaped 1-1/8" to size-specific lower headtube, compact race design, Zertz, internal cable routing, carbon OSBB
	S-Works Roubaix FACT carbon full monocoque, Zertz, size-specific, hollow carbon dropouts
	1-1/8" upper and size-specific lower, hybrid cartridge lightweight bearings, 8mm carbon cone spacer, w/ 20mm of carbon spacers
	OS integrated, CeramicSpeed, sealed ceramic bearings
	S-Works CG-R, FACT carbon w/ Zertz, 27.2mm
	Forged alloy, Ti bolt, 32.6mm

BIKE SPECS

	S-Works SL4 FACT 11r carbon, FACT construction, disc-specific, tapered/shaped 1-1/8" to size-specific lower headtube, compact race design, Zertz, internal cable routing, carbon OSBB
	S-Works Roubaix FACT carbon full monocoque, Zertz, size-specific
	1-1/8" upper and size-specific lower, hybrid cartridge lightweight bearings, 8mm carbon cone spacer, w/ 20mm of carbon spacers
	OS integrated, CeramicSpeed, sealed ceramic bearings
	S-Works CG-R, FACT carbon w/ Zertz, 27.2mm
	Forged alloy, Ti bolt, 32.6mm



Gloss Red/Carbon/White

S-WORKS SHIV DI2 X2

99114-0001	XS	Gloss Red/Carbon/White
99114-0002	SM	
99114-0003	MD	
99114-0004	LG	
99114-0005	XL	



BIKE SPECS

	S-Works Shiv FACT IS 11r carbon, FACT IS construction, crosswind-optimized airfoils, 1-1/8" lower bearing, OSBB, Control Tower Fit System, Fuelcelage Integrated Hydration System
	Specialized FACT Aero carbon monocoque, carbon steerer and crown for 1-1/8" bearing
	1-1/8" upper and lower, hybrid cartridge bearings
	Shiv Aerostem
	Specialized Carbon Aerobar
	Specialized S-Wrap w/ sticky gel
	Magura RT8TT caliper hydraulic
	Magura RT8TT caliper hydraulic
	Magura RT8TT caliper hydraulic brakes including adaptors and brake pads
	Shimano Dura-Ace Di2, 11-speed
	Shimano Dura-Ace Di2, 11-speed
	Shimano Dura-Ace Di2 TT levers, 11-speed
	Shimano Dura-Ace, 11-speed, 11-28
	Shimano Dura-Ace, 11-speed
	S-Works FACT carbon
	53/39 TT
	OS integrated, sealed bearings
	Nylon flat test ride, loose-ball, w/ reflectors
	Roval Rapide CLX 60
	Roval Rapide CLX 60
	S-Works Turbo, 220TPI, aramid bead, BlackBelt protection, 700x23c
	S-Works Turbo, 220TPI, aramid bead, BlackBelt protection, 700x23c
	Standard presta valve
	Body Geometry Sitero Pro, w/ SWAT Technology, tri-pod w/ bottle cage, carbon rails
	Shiv Aero FACT carbon, 12.5mm/37.5mm
	Shiv seat clamp
	Integrated hydration and frame-mounted Fuelcell



Satin/Gloss Carbon

S-WORKS SHIV MODULE X2

79114-0101	XS	Satin/Gloss Carbon
79114-0102	SM	
79114-0103	MD	
79114-0104	LG	
79114-0105	XL	



BIKE SPECS

	S-Works Shiv FACT IS 11r carbon, FACT IS construction, crosswind-optimized airfoils, 1-1/8" lower bearing, OSBB, Control Tower Fit System, Fuelselage Integrated Hydration System
	Specialized FACT Aero carbon monocoque, carbon steerer and crown for 1-1/8" bearing
	1-1/8" upper and lower, hybrid cartridge bearings
	Shiv Aerostem
	Specialized Carbon Aerobar
	Magura RT8TT caliper hydraulic
	Magura RT8TT caliper hydraulic
	Magura RT8TT caliper hydraulic brakes including adaptors and brake pads
	S-Works FACT carbon
	53/39 TT
	OS integrated, sealed bearings
	Shiv Aero FACT carbon, 12.5mm/37.5mm
	Shiv seat clamp
	Integrated hydration, frame-mounted Fuelcell compatible



Satin/Gloss Carbon/White

S-WORKS SHIV TT MODULE X2

79114-0201	XS	Satin/Gloss Carbon/White
79114-0202	SM	
79114-0203	MD	
79114-0204	LG	
79114-0205	XL	



BIKE SPECS

	Specialized FACT 11r carbon, aero tube shapes, FACT IS construction, includes fork, seatpost and stem, OSBB
	S-Works FACT full-carbon monocoque, UCI-legal
	1" upper and 1-1/8" lower, stainless steel cartridge bearings
	S-Works Shiv TT Aerostem
	S-Works TT Aerobar
	Aero integrated
	Aero integrated
	S-Works FACT carbon
	53/39 TT
	OS integrated, ceramic bearings
	Shiv Aero, FACT carbon, 400mm
	Integrated w/ frame



Satin/Gloss/Carbon/Red/White

S-WORKS CRUX CARBON RED DISC

99314-0049	49	Satin/Gloss/Carbon/Red/White
99314-0052	52	
99314-0054	54	
99314-0056	56	
99314-0058	58	
99314-0061	61	



BIKE SPECS

	S-Works FACT 11r carbon, disc-specific, 1-3/8" lower bearing, OSBB
	Specialized FACT carbon, disc-specific monocoque fork, carbon steerer and crown for 1-3/8" lower bearing
	1-1/8" upper and 1-3/8" lower hybrid cartridge lightweight bearings
	S-Works SL, 3D forged 7050 aluminum, 4-bolt, 31.8mm clamp
	Specialized CX Comp Shallow Bend, 6061 alloy, 125mm drop, 70mm reach
	Specialized S-Wrap HD
	SRAM RED, hydraulic disc, SRAM XX 160mm center-lock rotor
	SRAM RED, hydraulic disc, SRAM XX 140mm center-lock rotor
	SRAM RED, hydraulic disc
	SRAM RED 22, braze-on, 11-speed, YAW compatible, chain spotter
	SRAM RED 22, 11-speed
	SRAM RED 22, DoubleTap, 11-speed, integrated hydraulic brake system
	SRAM RED 22, 11-speed, 11-28
	SRAM RED 22 w/ PowerLock
	S-Works FACT carbon, OSBB
	SRAM RED 22, 46/36, YAW compatible
	OS integrated, CeramicSpeed sealed ceramic bearings
	Nylon flat test ride, loose ball, w/ reflectors
	Roval Rapide CLX 40 carbon disc tubular, w/ center lock hub, CeramicSpeed bearings
	Roval Rapide CLX 40 carbon disc tubular, w/ center lock hub, CeramicSpeed bearings
	Specialized Terra Tubular, 260TPI, 700x33c
	Specialized Terra Tubular, 260TPI, 700x33c
	Body Geometry Phenom Expert, hollow Ti rails, 143mm
	S-Works FACT carbon CG-R, single bolt, 27.2mm
	Forged alloy, Ti bolt, 32.6mm



Gloss Monster/Charcoal/White

S-WORKS CRUX CARBON DISC FRAMESET

79314-0249	49	Gloss Monster/Charcoal/White
79314-0252	52	
79314-0254	54	
79314-0256	56	
79314-0258	58	
79314-0261	61	



BIKE SPECS

	S-Works FACT 11r carbon, disc-specific, 1-3/8" lower bearing, OSBB
	Specialized FACT carbon, disc-specific monocoque fork, carbon steerer and crown for 1-3/8" lower bearing
	1-1/8" upper and 1-3/8" lower hybrid cartridge lightweight bearings
	OS integrated, CeramicSpeed ceramic sealed bearings
	S-Works FACT carbon CG-R, single bolt, 27.2mm
	Forged alloy, Ti bolt, 32.6mm



Satin/Gloss/Carbon/Red/White

S-WORKS CRUX CARBON FRAMESET

79314-0349	49	Satin/Gloss/Carbon/Red/White
79314-0352	52	
79314-0354	54	
79314-0356	56	
79314-0358	58	
79314-0361	61	



BIKE SPECS

	S-Works FACT 11r carbon, canti-specific, 1-3/8" lower bearing, OSBB
	Specialized FACT carbon, canti-specific monocoque fork, carbon steerer and crown for 1-3/8" lower bearing
	1-1/8" upper and 1-3/8" lower hybrid cartridge lightweight bearings
	OS integrated, CeramicSpeed ceramic sealed bearings
	S-Works FACT carbon CG-R, single bolt, 27.2mm
	S-Works, w/ brake stop, 32.6mm